

4G LTE INTERCOM SPECIFICATION

FEATURES AND BENEFITS



H 224 x W 96 x D 40

ML SOLO

316 marine grade stainless steel faceplate

- High strength, alloy cast back box
- LED downlight
- 40mm low profile backbox
- Stainless steel security screws
- Surface or flush mounted*
- Downward facing microphone
- **THS**[•] Horwood quality sound
- Call up to 8 numbers from a single call point
- 7 programmable colours
- IP 65 rated
- Time clock with 9 profiles
- 2 year warranty

*Stainless Steel Only

DOWNLOAD THE 'COMMTEL COMMAND ONE' APP



OPEN | HOLD | CLOSE AT THE CLICK OF A BUTTON

www.telguard.co.uk/support/downloads/apps.html

EASY TO USE

The single call button can ring through to up to 8 cascading landline or mobile phone numbers. Once answered, if the recipient wants to grant access to the visitor they simply press the # key on their phone.

DOWNLOADABLE ACTIVITY LOGS

Download the last 10,000 interactions with the unit and see who is gaining entry, how and when. A great security feature for free.

DIAL TO OPEN

Authorise up to 900 numbers the ability to call the unit and open your door/gate. A modern and more cost effective alternative to traditional access control.

EASY TO INSTALL

TWO YEAR WARRANTY

SPECIFICATIONS

- Power 12 Volt 1 Amp. DC PSU fitted with a 3A fuse (supplied and must be dedicated to the Telguard intercom unit). Power Consumption: 120 mA Idle @ 12 Volts.
- **Telephone Type** Standard DTMF (Dual Tone Multi Frequency) generating telephone, cordless or mobile phone.
- Programming Remotely programmable via App, SMS or via GSM modem. Locally via USB cable.
- **Relays** 3: 1 x 2A, 2 x 200mA, 2 x Auxiliary inputs.
- **Relay Activation Time** 1 60 seconds, adjustable locally and remotely.
- **Operating Commands** Default #, 2#, 3#, 4#, 5#, 6#, 7#, 8#, 9#. All relay commands are configurable.
- I Time Clocks This utilizes the on board time clock enabling custom profile functions to be activated.
- Authorised Call Access 900 telephone numbers can be stored. Calling the unit, from an authorised telephone number activates the relay.



Raising Standards Safety Assured

EU CE Declaration of Conformity and Radio Equipment Directive is available at www.commtel-uk.com | GB-RH10 9XN



